



Sliding contact surfaces: Steel / Zinc base alloy

Bearing number	Dimensions																	Static load ratings kN	Weight ≈kg
	$d_1$	$d_2$	$d_3$	$l$	$l_1$	$l_2$	$l_3$	$S_1$	$L$	$L_1$	$L_2$	$L_3$	$D_1$	$D_2$	$D_3$	$S_2$	$\alpha^\circ$ ≈		
SQ5-RS	M5	9	19	29	8	10	21	7	35	27	4	14	9	11	16	9	25	2.2	0.026
SQ6-RS	M6	10	20	35.5	11	11	26	8	40	30.5	5	14	10	13	19	11	25	3.5	0.039
SQ8-RS	M8	12	24	42.5	12	14	31	10	48	36.5	5	17	12.5	16	23	14	25	6.6	0.068
SQ10-RS	M10X1.25	14	30	50.5	15	17	37	11	57	43.5	6.5	21	15	19	27	17	25	10	0.112
SQ12-RS	M12X1.25	17	32	57.5	17	19	42	15	66	50.5	6.5	25	17.5	22	31	19	25	16	0.164
SQ14-RS	M14X1.5	19	38	73.5	22	21.5	56	17	75	57.5	8	26	20	25	35	22	25	19	0.254
SQ16-RS	M16X1.5	22	44	79.5	23	23.5	60	19	84	64.5	8	32	22	27	39	22	20	26	0.336
SQ18-RS	M18X1.5	23	45	90	25	26.5	68	20	93	71	10	34	25	31	44	27	20	33	0.464
SQ20-RS	M20X1.5	23	50	90	25	27	68	20	99	77	10	35	27.5	34	44	30	20	45	0.538
SQ22-RS	M22X1.5	27	52	95	26	28	70	24	109	84	12	41	30	37	50	32	16	48	0.713

The shank of ball joint housing may be left-hand thread, for left-hand thread, suffix "L" is added to bearing number and thread sign, e.g. SQL5-RS M5L-6H.

Bearing number	Dimensions																	Static load ratings kN	Weight ≈kg
	$d_1$	$d_2$	$d_3$	$l$	$l_1$	$l_2$	$l_3$	$S_1$	$L$	$L_1$	$L_2$	$L_3$	$D_1$	$D_2$	$D_3$	$S_2$	$\alpha^\circ$ ≈		
SQY4-RS	10-32	9	19	29	8	10	21	7	35	27	4	14	9	11	16	9	25	2.2	0.026
SQY6-RS	1/4-28	10	20	35.5	11	11	26	8	40	30.5	5	14	10	13	19	11	25	3.5	0.039
SQY7-RS	5/16-24	12	24	42.5	12	14	31	10	48	36.5	5	17	12.5	16	23	14	25	6.6	0.068
SQY9-RS	3/8-24	14	30	50.5	15	17	37	11	57	43.5	6.5	21	15	19	27	17	25	10	0.112
SQY11-RS	7/16-20	17	32	57.5	17	19	42	15	66	50.5	6.5	25	17.5	22	31	19	25	16	0.164
SQY12-RS	1/2-20	19	38	73.5	22	21.5	56	17	75	57.5	8	26	20	25	35	22	25	19	0.254
SQY15-RS	5/8-18	22	44	79.5	23	23.5	60	19	84	64.5	8	32	22	27	39	22	20	26	0.336
SQY19-RS	3/4-16	23	45	90	25	26.5	68	20	93	71	10	34	25	31	44	27	20	33	0.464

The shank of ball joint housing may be left-hand thread, for left-hand thread, suffix "L" is added to bearing number and thread sign, e.g. SQYL4-RS 10-32UNF-2BLH.

