



661



Body Mounting Base Horizontal With Welding, Tied Front

MODEL NO	F1 (N)	F3 (N)	F1 (N)	Vn (dm ³)	STROK	(WEIGHT) (gr)	BAR
661 - 3 (Ø 12)	1500	2960	300	0.25	23	860	6
661 - 3 (Ø 14)	2500	3200	500	0.51	23	1010	6
661 - 4 (Ø 16)	4500	6650	750	1.04	33	1800	6
661 - 4 (Ø 18)	4500	7200	750	1.04	33	1830	6
661 - 5 (Ø 20)	7500	15000	1100	2	42	3220	6

F1 : BASKI KUVVETİ (EXERTING FORCE) , F3 : TUTMA KAPASİTESİ (HOLDING CAPACITY) , F1 : UYGULAMA KUVVETİ (APPLIED FORCE)

Vn , 6 BAR BASINÇTA ÇİFT HAREKET İÇİN HAVA TÜKETİM MİKTARIDIR (Vn , AIR CONSUMPTION PER DOUBLE STROKE IN dm³ AT 6 BAR)

Pneumatic cylinders are double acting, magnetic and cushioning

MODEL NO	A	A2	B	B2	C	D	E	E2	F	G	H	J	K	L	M	N	P	R	PİSTON Ø
661 - 3 (Ø 12)	56	90	51	68	70		32,5 - 41		35 - 41	35	72	12	M8	292		7 x 12	Ø 10	G1/8	25
661 - 3 (Ø 14)	56	100	58	68	70		32,5 - 41		35 - 41	35	79	14	M8	312		7 x 12	Ø 12	G1/8	32
661 - 4 (Ø 16)	64	115	77	78	84		34,5 - 42,5		41	43	100	16	M10	372		9,5 x 13,5	Ø 16	G1/8	40
661 - 4 (Ø 18)	64	115	77	78	84		34,5 - 42,5		41	43	100	18	M10	372		9,5 x 13,5	Ø 16	G1/8	40
661 - 5 (Ø 20)	100	170	79	92	101		61,5 - 75	34,5 - 41,5	37 - 54	51	110	20	M12	456		11 x 22	Ø 20	G1/8	50

