



Sliding contact surfaces: Steel / PTFE fabric

Bearing number	Dimensions mm/inch								Load ratings kN		Weight ≈ kg
	d	D	B	C	dk	rs min	r1s min	α° ≈	Dynamic	Static	
GEFZ4T	4.83	14.29	7.14	5.54	10.31	0.3	0.38	11	7.4	11	0.006
	0.19	0.5625	0.281	0.218	0.406	0.012	0.015				
GEFZ6T	6.35	16.67	8.71	6.35	12.70	0.3	0.56	13	10	15	0.010
	0.25	0.6562	0.343	0.25	0.5	0.012	0.022				
GEFZ7T	7.94	19.05	9.53	7.14	14.27	0.3	0.81	11	13	19	0.014
	0.3125	0.75	0.375	0.281	0.562	0.012	0.032				
GEFZ9T	9.53	20.64	10.31	7.92	16.66	0.3	0.81	9	17	25	0.018
	0.375	0.8125	0.406	0.312	0.656	0.012	0.032				
GEFZ11T	11.11	23.02	11.10	8.71	17.45	0.3	0.81	9	19	28	0.021
	0.4375	0.9062	0.437	0.343	0.687	0.012	0.032				
GEFZ12T	12.70	25.40	12.70	9.91	20.65	0.3	0.81	9	26	39	0.029
	0.5	1	0.5	0.39	0.813	0.012	0.032				
GEFZ14T	14.29	27.78	14.27	11.10	23.01	0.3	0.81	9	33	49	0.042
	0.5625	1.0937	0.562	0.437	0.906	0.012	0.032				
GEFZ15T	15.88	30.16	15.88	12.70	25.40	0.3	0.81	8	41	61	0.053
	0.625	1.1875	0.625	0.5	1	0.012	0.032				
GEFZ19T	19.05	36.51	19.05	15.06	30.15	0.3	1.12	9	59	88	0.094
	0.75	1.4375	0.75	0.593	1.187	0.012	0.044				
GEFZ22T	22.23	39.69	22.23	17.86	33.32	0.6	1.12	9	89	133	0.119
	0.875	1.5625	0.875	0.703	1.312	0.024	0.044				
GEFZ25T	25.40	44.45	25.40	20.24	38.10	0.6	1.12	9	115	172	0.173
	1	1.75	1	0.797	1.5	0.024	0.044				

