



Sliding contact surfaces: Steel / Steel

SI...E

SI...ES、SIS...ES

Bearing number	Dimensions mm																Load Ratings kN		Weight ≈kg
	d	B	d _K	C ₁ max	d ₂	G 6H	h ₁	l ₃ min	l ₄	l ₅	l ₇	W	d ₃	d ₄	r _s min	α° ≈	Dynamic	Static	
SI5E ¹⁾	5	6	10	4.5	21	M5	30	11	40.5	5	11.5	10	10	13	0.3	13	3.4	8.1	0.023
SI6E ¹⁾	6	6	10	4.5	21	M6	30	11	40.5	5	11.5	11	11	13	0.3	13	3.4	8.1	0.023
SI8E ¹⁾	8	8	13	6.5	24	M8	36	15	48	5	13	13	13	16	0.3	15	5.5	12.9	0.040
SI10E ¹⁾	10	9	16	7.5	29	M10	43	20	57.5	6.5	15	16	16	19	0.3	12	8.1	17.6	0.065
SI12E ¹⁾	12	10	18	8.5	34	M12	50	23	67	7	18	18	19	22	0.3	10	10	24.5	0.108
SI15ES ²⁾	15	12	22	10.5	40	M14	61	30	81	8	21	21	21	26	0.3	8	16	36	0.169
SI17ES ²⁾	17	14	25	11.5	46	M16	67	34	90	10	24	27	25	29	0.3	10	21	45	0.235
SI20ES ²⁾	20	16	29	13.5	53	M20X1.5	77	40	103.5	10	25.5	30	28	34	0.3	9	30	60	0.335
SI25ES	25	20	35.5	18	64	M24X2	94	48	126	12	33	36	35	42	0.6	7	48	83	0.665
SI30ES	30	22	40.7	20	73	M30X2	110	56	146.5	15	37.5	46	42	50	0.6	6	62	110	1.05
SI35ES	35	25	47	22	82	M36X3	125	60	166	15	40	55	48	58	0.6	6	79	146	1.50
SI40ES	40	28	53	24	92	M39X3	142	65	188	18	47	60	52	65	0.6	7	99	180	2.05
SIS40ES	40	28	53	24	92	M42X3	142	65	188	18	47	55	52	65	0.6	7	99	180	1.94
SI45ES	45	32	60	28	102	M42X3	145	65	196	20	52	65	58	70	0.6	7	127	240	2.72
SIS45ES	45	32	60	27	102	M45X3	145	65	196	20	52	60	58	70	0.6	7	127	240	2.61
SI50ES	50	35	66	31	112	M45X3	160	68	216	20	57	70	62	75	0.6	6	156	290	3.48
SIS50ES	50	35	66	31	112	M52X3	160	69	216	20	57	65	62	75	0.6	6	156	260	3.24
SI60ES	60	44	80	39	135	M52X3	175	70	242.5	20	68.5	80	70	88	1	6	245	450	5.55
SIS60ES	60	44	80	39	135	M60X4	175	73	242.5	20	68.5	75	70	88	1	6	245	300	4.99
SI70ES	70	49	92	43	160	M56X4	200	80	280	20	81	85	80	98	1	6	313	610	8.72
SIS70ES	70	49	92	42	160	M72X4	200	80	280	20	81	80	85	98	1	6	313	470	8.33
SI80ES	80	55	105	48	180	M64X4	230	85	320	25	91	95	95	110	1	6	400	750	12.9
SIS80ES	80	55	105	47	180	M80X4	230	85	320	25	91	100	95	110	1	6	400	600	11.7

Can not be relubricated.

Can only be relubricated through the rod end housing.

Can supply other rod ends with different pitch or accuracy of thread.

For left-hand thread, suffix "L" is added to bearings number and thread sign, e.g. SIL20ES M20X1.5L-6H.

