



Sliding contact surfaces: Steel / PTFE plastic

Bearing number	Dimensions mm									Load ratings kN		Weight ≈kg
	d	D	B	C	T	d <sub>k</sub>	S	r <sub>s</sub> , r <sub>1s</sub> min	α° ≈	Dynamic	Static	
GAC25N	25	47	15	14	15	42	0.6	1	2.5	20	32	0.148
GAC30N	30	55	17	15	17	49.5	1.3	1	4.5	26	41	0.208
GAC35N	35	62	18	16	18	55.5	2.1	1	4	31	49	0.268
GAC40N	40	68	19	17	19	62	2.8	1	3.5	36	59	0.327
GAC45N	45	75	20	18	20	68.5	3.5	1	3	43	69	0.416
GAC50N	50	80	20	19	20	74	4.3	1	1.5	49	78	0.455
GAC60N	60	95	23	21	23	88.5	5.7	1.1	2.5	65	104	0.714
GAC70N	70	110	25	23	25	102	7.2	1.1	2	82	131	1.04
GAC80N	80	125	29	25.5	29	115	8.6	1.1	3.5	102	164	1.54
GAC90N	90	140	32	28	32	128.5	10.1	1.5	3.5	125	201	2.09
GAC100N	100	150	32	31	32	141	11.6	1.5	0.5	152	244	2.34
GAC110N	110	170	38	34	38	155	13	2	3	184	295	3.68
GAC120N	120	180	38	37	38	168	14.5	2	0.5	217	348	3.97

