

## EP81-105 SERIES (13 SW) Polyamide Articulated Feet

CODE	D (mm)	M	L (mm)	L1 (mm)	H (mm)	Load kg / pcs
EP81 0845	81	M8x45	75	45	30	600
EP81 0860	81	M8x60	90	60	30	600
EP81 1045	81	M10x45	75	45	30	600
EP81 1060	81	M10x60	90	60	30	600
EP81 1075	81	M10x75	105	75	30	600
EP81 1090	81	M10x90	120	90	30	600
EP81 1012	81	M10x120	150	120	30	600
EP81 1245	81	M12x45	75	45	30	600
EP81 1260	81	M12x60	90	60	30	600
EP81 1275	81	M12x75	105	75	30	600
EP81 1290	81	M12x90	120	90	30	600
EP81 1212	81	M12x120	150	120	30	600
EP105 0845	105	M8x45	80	45	35	800
EP105 0860	105	M8x60	95	60	35	800
EP105 1045	105	M10x45	80	45	35	800
EP105 1060	105	M10x60	95	60	35	800
EP105 1075	105	M10x75	110	75	35	800
EP105 1090	105	M10x90	125	90	35	800
EP105 1012	105	M10x120	155	120	35	800
EP105 1245	105	M12x45	80	45	35	800
EP105 1260	105	M12x60	95	60	35	800
EP105 1275	105	M12x75	110	75	35	800
EP105 1290	105	M12x90	125	90	35	800
EP105 1212	105	M12x120	155	120	35	800

(Floor mount option)

### CONNECTION FLAT POLYAMIDE FOOT

It is a polyamide-based, articulated bolt.  
Add the standard product code (L) for the addition of the anti-slip rubber pad to the nut (S).

