


## » Part name and description

Safer equipment management, Smoother, quieter overall operational movement, Easy installation, Patented new Revolving Chain from CPS, Revolving Chain adopt the latest technological efforts with customer requests for larger, smoother and quieter ranges of movement, Revolving Chain's abilities stretch even further, made possible thanks to the patented free-bending radius. So whether or not your operating equipment is moving a full range of more than 360degrees continuously, or if it is moving in different shorter movements, Revolving Chain protects your cables while allowing the equipment to move freely throughout the full range of motion.



### 1 Easy Bracket

The end of the cable chain, used to mount the application to the operating machinery or moving apparatus, CPS has improved the end bracket by making it possible to mount the cable chain from the front, side, bottom or top.

### 5 Stopper

It is a unit to adjust the divider's position by considering number of cables in cable chain.

### 2 Side Band


Developed and patented by CPS, As a result of the sideband connection method, virtually no noise is produced during operation, Which is possible by eliminating all points of friction.

### 6 Ball Caster

Attached to the bottom of the sidebands, ball casters help to facilitate smooth and quiet movement of the cable chain, CPS ball casters are used every 8 link. (Can be changed according to application environment)

### 3 Frame

It is a unit that connects to side band and inner surface is smoothly machined to protect cables from friction.



**Adjustable Bending Radius per 1mm!**


Revolving Chain adjusts to the machine or application movement by creating various bending radius automatically. It can be adjusted by a unit of 1mm.

### 4 Divider & Separator

Used to separate the cables inside of the cable chain and protect them from twisting and breaking.


## » Stopper System

Stopper decides the location of divider which is settled in side of cable chain and control the position of divider according to the inserted cable's size and quantity. The items are classified as ST-M1, ST-M2, ST-S1, ST-S2 and please refer following drawings.




## » Ordering

**RV 048CR, 200, A / F - 1000L : 10ST**




## RV040CR

### » Chain cross section




Type A	Minimum distance (L)	230
	Minimum reverse bending (R)	120
Type B	Minimum distance (L')	340
	Minimum reverse bending (R')	70

There are two installation choices, A or B corresponding with the bending radius of the side band, Choose A or B installation when there is insufficient distance between R, R' (Inner Bending Radius) and L, L' (Reverse)



Chain Type	A (A1)	B	C	D (D1)
RV 040CR	78 (86)	52	50	40(37)
	103 (111)		75	
	128 (136)		100	
	138 (146)		110	
	153 (161)		125	
	178 (186)		150	
	203 (211)		175	
	228 (236)		200	


### » Bracket type



Chain Type	Pitch	C
RV 040CR	40	50
		75
		100
		110
		125
		150
		175
		200


(Dimensions in mm)

### » Application method stopper




### » Dividers(DV)

Divider is used when there are more than 2 cables are inserted, which protects twisting and beaking problem.



(Dimensions in mm)

### » Separators(SP)



The inserted separators into dividers have the function to separate cables, and lessen the interference of cables, so as it is also used for efficient use of inner chamber space.

Ordering NO.	Length (L)
S-SP/M,50	50
S-SP/M,75	75
S-SP/M,100	100
S-SP/M,110	110
S-SP/M,125	125
S-SP/M,150	150
S-SP/M,175	175
S-SP/M,200	200

(Dimensions in mm)

